

MediaPack™ Series Analog VoIP Gateways (MP-11X, MP-124D)



- Provides voice, fax and modem support
- Offers toll quality voice compression
- Enhanced capabilities including MWI, long haul, Metering Tones Generation, CID and outdoor protection
- Allows Fallback to PSTN for E911 or upon network/power failure (FXO and /or FXS) configurations
- Supports Stand Alone Survivability (SAS) for IP Centrex and Central IP-PBX
- Supports SIP, H.323 and MGCP standard control protocols
- Proven integration with leading PBXs, IP-PBXs, Softswitches and Gatekeepers



The **MediaPack™ Series** Analog VoIP Gateways are cost-effective, best-of-breed technology products. These stand-alone analog VoIP Gateways provide superior voice technology for connecting legacy telephones, fax machines and PBX systems with IP-based telephony networks, as well as for integration with new IP-based PBX systems. These products are designed and tested to be fully interoperable with leading Softswitches, SIP servers and H.323 gatekeepers.

MediaPacks are well suited for commercial VoIP deployment because of their mature and field-proven voice and fax technology. Their rich feature set allows integration with a wide range of Carriers and Enterprise network applications. MediaPack gateways are used by Carriers and Service Providers in Access networks for connecting Multi-Tenant Units (MTU), IP-Centrex subscribers, payphones and rural users over various wireless and satellite links. Enterprises use MediaPack gateways to connect their legacy PBX systems over an IP infrastructure. In addition, in IP Centrex and central IP-PBX applications, the MediaPack increases the remote location availability and provides Stand Alone Survivability (SAS) when there is no IP connection between branch locations and the central SIP servers, SIP Proxy or central IP-PBX.

DELIVER FEATURE-RICH SOLUTIONS

MediaPacks are third generation products that have been designed to meet real market needs. In addition to superior voice technology, the products provide advanced telephony features such as long-haul, metering tones generation, country dependent MWI and CID for true integration with the existing telephony infrastructure. A variety of management and provisioning tools, such as AudioCodes' EMS, embedded web server, Telnet and SNMP enable fast deployment and management of large and complex networks. MediaPacks are based on VoIPerfect™ architecture, AudioCodes underlying, best-of-breed, core media gateway technology for all of its products.

PROVIDE INTEROPERABILITY

MediaPacks are part of AudioCodes' complete family of stand-alone VoIP Gateways for OEM system integration. Throughout the years, AudioCodes has invested significant effort in complying with the leading and evolving VoIP standards. Support of multiple VoIP control protocols has been tested with leading Softswitch vendors. As a provider for OEMs, System Integrators and Network Equipment Providers, AudioCodes offers short time-to-market with field-proven products.

BENEFIT FROM EXTENSIVE EXPERIENCE

AudioCodes, established in 1993, is one of the world's leading providers of VoIP technology. AudioCodes' commitment to innovation yields consistently high-quality voice processing products that are feature-rich and field-proven. AudioCodes has deployed tens of millions of VoIP ports in over 100 countries to date.

MEDIAPACK SERIES FEATURES

- Spans a range of 2 to 24 analog ports
- Supports PSTN/PBX analog telephone sets or analog trunk lines (FXS/FXO)
- Selectable, multiple LBR coders per channel
- T.38 compliant
- Echo cancellation, Jitter Buffer, VAD and CNG
- Complies with MGCP, H.323 (V4) and SIP control protocols
- Enhanced capabilities which include MWI, long-haul, Metering Tones, STUN, Security features, Generation, CID and outdoor protection
- Stand Alone Survivability (SAS) for SIP based IP Centrex and Central IP-PBX applications
- Web Management for easy configuration and installation
- EMS for comprehensive management operations (FCAPS)
- Automatic provisioning via TFTP/HTTP
- Internal Access List firewall for network traffic filtering

AudioCodes CPE & Access Gateway Products

MediaPack™ Series

SPECIFICATIONS

	MP-112	MP-114 and MP-118	MP-124D
Interfaces			
Voice Ports	2 ports	4 and 8 ports	24 ports
Telephone Interfaces	FXS, RJ11	FXS, FXO or mixed FXS/FXO, RJ11	FXS, 50-pin Telco Connector
Lifeline	Automatic cut through of a single analog line		
Network Interface	10/100 BASE-TX, RJ45		
Indicators	Channel status and activity LEDs		
Voice, Fax, Modem			
Voice over Packet	G.168-2004 compliant Echo Cancellation, VAD, CNG, Dynamic programmable Jitter		
Capabilities	Buffer, modem detection and auto-switch to PCM		
Voice Compression	G.711, G.723.1, G.726, G.729A		
Fax over IP	T.38 compliant		
	Group 3 fax relay up to 14.4 kbps with automatic switching to PCM or ADPCM		
QoS	Diffserve, TOS, 802.1 P/Q VLAN tagging		
IP Transport	RTP/RTCP per IETF RFC 3550 and 3551 PPPoE, ThruPacket™ (aggregated RTP streams of several channels for saving network bandwidth)		
Signaling			
Signaling	FXS Loop-start	FXS, FXO Loop-start	FXS Loop-start
In-band Signaling	DTMF (TIA 464B) User-defined and call progress tones		
Control	MGCP (RFC 2-05), H.323 (V4), SIP (RFC 3261)		
Provisioning	BootP, DHCP, TFTP and HTTP for Automatic Installation Remote management using Web browser EMS (Element Management System) Syslog support RS-232 for basic configuration Voice Menu using touch tone phone for basic configuration		
Security			
Media	SRTP		
Control	H.235, IPSEC, TLS/SIPS		
Management	HTTPS, Access List, IPSEC		
Physical			
Power	100-240 V AC/50-60 Hz or -48V DC*		
Environmental	Operational: 5 to 40° C 41 to 104° F Storage: -25 to 85° C -13 to 185° F Humidity: 10 to 90% non-condensing		
Dimensions (HxWxD)	42x172x220mm	42x172x220mm	44x445x269mm
Mounting	Rack mount, Table top, Wall mount		
Additional Features			
Message Waiting Indication	Applying 100V DC on line for lighting bulb in handset		
High Availability	PSTN Fallback: Support of PSTN fallback due to Power failure of if the IP connection is down or customer defined if IP QOS thresholds Supported in all ports of Mixed FXS/FXO and in first port of MP-114/FXS and MP-118/FXS using special Lifeline cable Stand Alone Survivability (SAS): Supports SAS of up to 30 SIP users (UA) per MediaPack REN3: Up to 9Km (24 AWG line)		
Short and Long Haul	Bellcore GR-30-CORE Type 1 using Bell 202 FSK modulation, ETSI Type 1, NTT, Denmark, India, Brazil, British and DTMF ETSI CID (ETS 300-659-1)		
Caller ID	Bellcore GR-30-CORE Type 1 using Bell 202 FSK modulation, ETSI Type 1, NTT, Denmark, India, Brazil, British and DTMF ETSI CID (ETS 300-659-1)		
Polarity Reversal / Wink	Immediate or smooth to prevent erroneous ringing		
Metering Tones	12/16 KHz sinusoidal bursts, Generation on FXS		
Distinctive Ringing	By frequency (15-100 Hz) and cadence patterns		
Message Waiting Indication	DC voltage generation (TIA/EIA-464-B), V23 FSK data, Stutter Dial Tone		
Outdoor Protection	Over-voltage protection and surge immunity		
Homologation			
EMC	EN55022 Class B, CFR Part 15 Class B, EN55024, EN61000-3-3, EN61000-3-2, VCCI Class X1 (equal to class B)		
Safety	UL60950-1 Safety of information technology equipment, UL60950-1 Including compliance to section 6 (over-voltage protection)		
Telecom	TRR-21, TIA-968		

* -48V DC is supported only in the MP-124D

APPLICATIONS

- Survivable IP Centrex for hosted services and central IP-PBX IP Centrex for hosted services
- Multi-Tenant Units
- POTs and fax extensions for IP-PBX
- Voice VPN
- VoIP-enabled PBX
- Unified Messaging and recording
- IP-PBX FXS Analog extensions and FXO Trunking

ABOUT AUDIOCODES

AudioCodes Ltd. (NASDAQ: AUDC) provides innovative, reliable and cost-effective Voice over IP (VoIP) technology, Voice Network Products, and Value Added Applications to Service Providers, Enterprises, OEMs, Network Equipment Providers and System Integrators worldwide. AudioCodes provides a diverse range of flexible, comprehensive media gateway, and media processing enabling technologies based on VoIPerfect™ – AudioCodes' underlying, best-of-breed, core media architecture. The company is a market leader in VoIP equipment, focused on VoIP Media Gateway, Media Server, Session Border Controllers (SBC), Security Gateways and Value Added Application network products. AudioCodes has deployed tens of millions of media gateway and media server channels globally over the past ten years and is a key player in the emerging best-of-breed, IMS based, VoIP market. The Company is a VoIP technology leader focused on quality and interoperability, with a proven track record in product and network interoperability with industry leaders in the Service Provider and Enterprise space. AudioCodes Voice Network Products feature media gateway and media server platforms for packet-based applications in the converged, wireline, wireless, broadband access, cable, enhanced voice services, video, and Enterprise IP Telephony markets. AudioCodes' headquarters are located in Israel with R&D in the U.S. Other AudioCodes' offices are located in Europe, India, the Far East, and Latin America.

International Headquarters

1 Hayarden Street,
Airport City
Lod 70151, Israel
Tel: +972-3-976-4000
Fax: +972-3-976-4040

US Headquarters

2099 Gateway Place, Suite 500
San Jose, CA 95110
Tel: +1-408-441-1175
Fax: +1-408-451-9520

Contact us: www.audiocodes.com/info
Website: www.audiocodes.com

© 2007 All rights reserved. AudioCodes, AC, Ardito, AudioCoded, NetCoder, TrunkPack, VoicePacketizer, MediaPack, Stretto, Mediant, VoIPerfect and IPmedia, OSN, Open Solutions Network, What's Inside Matters, Your Gateway To VoIP, 3GX and Nuera, Netrake, InTouch, CTI and CTI Squared are trademarks or registered trademarks of AudioCodes Limited. All other products or trademarks are property of their respective owners.

Ref # LTRM-30010 09/07 Rev. 04

